


I-TRAP 75E

www.insect-trap.net



**The discrete 120 m² wall mounted
insect control unit**



I-TRAP 75E

i-trap 75E wall mounting system.

With its innovative design, the i-trap 75E is recommended for use in homes, offices, shops and restaurants. The i-trap has a specially designed front grid which optimizes the attraction potential. The cover/grid is made of ABS plastic and the casing of coated steel.

Once the insects enter the i-trap, they will be effectively controlled by means of a centrally placed glue board.

Easy to service, stylish and effective; the i-trap 75E offers it all.

10 reasons to start using the i-trap 75E:

- 1) In its wall mounted position the unit is very discrete.
- 2) Unit can be used in a wide variety of applications.
- 3) Glue board discreetly placed out of sight and is easy to replace.
- 4) Coated steel (Metal housing) offers durability.
- 5) Effective coverage of areas up to 120 m².
- 6) Easy to service with direct access to lamp and glue board
- 7) Meets ISO 9001 / RoHS & the CE standard.
- 8) Durable quality components, industrial design.
- 9) High powered effective UV-A lamp.
- 10) 2 year full guarantee on the mechanical aspects.



**Powered by Philips
Longlife UV-A**



asimpleswitch.com

Technical specifications

Area coverage (m ²)	: 120 m ² (1250 ft ²)
Light source	: 3 x 15 watt Philips Long-life shatterproof UV-A
Type of UV lamps	: UV Lamps RoHS certified
Electrical supply (V)	: 110-240V ~ 50/60Hz
Catch specifications	: By means of Temperature Optimized Glueboard
Power consumption	: 49 W
Weight (kg)	: 6
Material	: Coated steel casing, cover/grid ABS plastic
Degree of protection	: IP20 (Safe to use in dry environments)
Guarantee	: 2 years return to base
Int. building norm	: acc. EN 60335-2-59 int. std. for insect traps
Lamp life time (h)	: 17.500
Dimensions (L x D x H)	: 520 x 150 x 365 mm (20 x 6 x 13,5 inches)
CE-approval	: Yes
Mounting position	: Wall mounted
Cable & plug	: Included
Packging	: Strong cardboard box
Manual:	: Enclosed with the unit in English
Service	: Unit can be serviced without special tools

(*) After 17,500 hours of use, the Longlife lamp still offers 75% of its initial UVA output value